


2SC3876

NPN Silicon Epitaxial Planar Transistor
for switching and AF amplifier applications.

The transistor is subdivided into two groups, O and Y and according to its DC current gain.

On special request, these transistors can be manufactured in different pin configurations.




1. Emitter 2. Collector 3. Base
TO-92 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	35	V
Collector Emitter Voltage	V_{CEO}	30	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current	I_C	500	mA
Base Current	I_B	50	mA
Power Dissipation	P_{tot}	150	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 1 \text{ V}$, $I_C = 100 \text{ mA}$ at $V_{CE} = 6 \text{ V}$, $I_C = 400 \text{ mA}$	h_{FE} h_{FE} h_{FE}	70	-	140	-
		120	-	240	-
		25	-	-	-
Collector Base Cutoff Current at $V_{CB} = 35 \text{ V}$	I_{CBO}	-	-	0.1	μA
Emitter Base Cutoff Current at $V_{EB} = 5 \text{ V}$	I_{EBO}	-	-	0.1	μA
Collector Emitter Saturation Voltage at $I_C = 100 \text{ mA}$, $I_B = 10 \text{ mA}$	$V_{CE(sat)}$	-	0.1	0.25	V
Base Emitter Voltage at $I_C = 100 \text{ mA}$, $V_{CE} = 1 \text{ V}$	V_{BE}	-	0.8	1	V
Transition Frequency at $V_{CE} = 6 \text{ V}$, $I_C = 20 \text{ mA}$	f_T	-	300	-	MHz
Collector Output Capacitance at $V_{CB} = 6 \text{ V}$, $f = 1 \text{ MHz}$	C_{ob}	-	7	-	pF



SEMTECH ELECTRONICS LTD.



ISO/TS 16949:2009
Certificate No. 160713009



ISO 14001 : 2004
Certificate No. 7116



ISO 9001 : 2008
Certificate No. 60713410



BS-OHSAS 18001 : 2007
Certificate No. PRC-HSPM-1483-1



IECQ QC 090000
Certificate No. PRC-HSPM-1483-1