




## TO-220-3L Plastic-Encapsulate MOSFETS

### CJP02N60 N-Channel Power MOSFET

#### General Description

The high voltage MOSFET uses an advanced termination scheme to provide enhanced voltage-blocking capability without degrading performance over time. In addition, this advanced MOSFET is designed to withstand high energy in avalanche and commutation modes. The new energy efficient design also offers a drain-to-source diode with a fast recovery time. Designed for high voltage, high speed switching applications in power suppliers, converters and PWM motor controls, these devices are particularly well suited for bridge circuits where diode speed and commutating safe operating areas are critical and offer additional and safety margin against unexpected voltage transients.



#### FEATURES

- Robust High Voltage Termination
- Avalanche Energy Specified
- Source-to-Drain Diode Recovery Time Comparable to a Discrete Fast Recovery Diode
- Diode is Characterized for Use in Bridge Circuits
- $I_{DSS}$  and  $V_{DS(on)}$  Specified at Elevated Temperature

#### Maximum ratings ( $T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	600	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	
Continuous Drain Current	$I_D$	2	A
Pulsed Drain Current	$I_{DM}$	8	
Power Dissipation	$P_D$	2	W
Single Pulsed Avalanche Energy*	$E_{AS}$	128	mJ
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	$^\circ\text{C}/\text{W}$
Junction Temperature	$T_J$	150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-50 ~+150	

\* $E_{AS}$  condition:  $T_J=25^\circ\text{C}$ ,  $V_{DD}=50\text{V}$ ,  $L=64\text{mH}$ ,  $I_{AS}=2\text{A}$ ,  $R_G=25\Omega$

### Electrical characteristics (T<sub>a</sub>=25°C unless otherwise noted)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V <sub>(BR) DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> =250μA	600			V
Gate-Threshold Voltage (note1)	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	2.0		4.0	
Gate-Body Leakage Current (note1)	I <sub>GSS</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V			±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =600V, V <sub>GS</sub> =0V			25	μA
Drain-Source On-State Resistance (note1)	R <sub>DS(on)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =1A			4.4	Ω
Forward Transconductance (note1)	g <sub>FS</sub>	V <sub>DS</sub> =50V, I <sub>D</sub> =1A	1			S
Input Capacitance (note 2)	C <sub>iss</sub>	V <sub>DS</sub> =25V, V <sub>GS</sub> =0V, f =1MHz		435		pF
Output Capacitance (note 2)	C <sub>oss</sub>			56		
Reverse Transfer Capacitance (note 2)	C <sub>rss</sub>			9.2		
Turn-On Delay Time (note 2)	t <sub>d(on)</sub>	V <sub>DD</sub> =300V, I <sub>D</sub> =2A, V <sub>GS</sub> =10V, R <sub>G</sub> =18Ω		12		ns
Rise Time (note 2)	t <sub>r</sub>			21		
Turn-Off Delay Time (note 2)	t <sub>d(off)</sub>			30		
Fall Time (note 2)	t <sub>f</sub>			24		
Forward on Voltage(note1)	V <sub>SD</sub>	V <sub>GS</sub> =0V, I <sub>S</sub> =2A			1.6	V

**Notes:**


1. Pulse Test : Pulse width≤300μs, duty cycle ≤2%.
2. These parameters have no way to verify.

# Typical Characteristics


**Output Characteristics**




**Transfer Characteristics**




**$R_{DS(on)}$  —  $I_D$**




**$R_{DS(on)}$  —  $V_{GS}$**




**$I_S$  —  $V_{SD}$**



**Threshold Voltage**



# TO-220-3L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	4.470	4.670	0.176	0.184
A1	2.520	2.820	0.099	0.111
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.310	0.530	0.012	0.021
c1	1.170	1.370	0.046	0.054
D	10.010	10.310	0.394	0.406
E	8.500	8.900	0.335	0.350
E1	12.060	12.460	0.475	0.491
e	2.540 TYP		0.100 TYP	
e1	4.980	5.180	0.196	0.204
F	2.590	2.890	0.102	0.114
h	0.000	0.300	0.000	0.012
L	13.400	13.800	0.528	0.543
L1	3.560	3.960	0.140	0.156
$\Phi$	3.735	3.935	0.147	0.155