


MMBTSC2785

NPN Silicon Epitaxial Planar Transistor

for switching and AF amplifier applications.

The transistor is subdivided into four groups O, Y, G and L, according to its DC current gain.



On special request, these transistors can be manufactured in different pin configurations.

1. Base 2. Emitter 3. Collector


TO-236 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	60	V
Collector Emitter Voltage	V_{CEO}	50	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current	I_C	150	mA
Power Dissipation	P_{tot}	200	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	- 55 to + 150	°C

Characteristics at $T_{amb}=25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 6 \text{ V}$, $I_C = 1 \text{ mA}$	$\text{Current Gain Group}$				
O	h_{FE}	70	-	140	-
Y	h_{FE}	120	-	240	-
G	h_{FE}	200	-	400	-
L	h_{FE}	350	-	700	-
Collector Base Cutoff Current at $V_{CB} = 40 \text{ V}$	I_{CBO}	-	-	100	nA
Emitter Base Cutoff Current at $V_{EB} = 3 \text{ V}$	I_{EBO}	-	-	100	nA
Collector Base Breakdown Voltage at $I_C = 100 \mu\text{A}$	$V_{(BR)CBO}$	60	-	-	V
Collector Emitter Breakdown Voltage at $I_C = 10 \text{ mA}$	$V_{(BR)CEO}$	50	-	-	V
Emitter Base Breakdown Voltage at $I_E = 10 \mu\text{A}$	$V_{(BR)EBO}$	5	-	-	V
Collector Emitter Saturation Voltage at $I_C = 100 \text{ mA}$, $I_B = 10 \text{ mA}$	$V_{CE(\text{sat})}$	-	-	0.3	V
Gain Bandwidth Product at $V_{CE} = 6 \text{ V}$, $I_C = 10 \text{ mA}$	f_T	-	300	-	MHz
Output Capacitance at $V_{CB} = 6 \text{ V}$, $f = 1 \text{ MHz}$	C_{ob}	-	2.5	-	pF



SEMTECH ELECTRONICS LTD.



ISO TS 16949 : 2009 ISO 14001 : 2004 ISO 9001 : 2008 BS-OHSAS 18001 : 2007 IECQ QC 080000

Certificate No. 160719000 Certificate No. 7116 Certificate No. 50713410 Certificate No. 7116 Certificate No. PRC-HSPM-1403-1

Dated: 16/03/2015 Rev: 01